


## Single Mode VCSEL 850 nm with Photodiode, 1 mW



**IMV-850-1-PL-TO46 with photodiode**  
850 nm polarization locked single mode VCSEL in TO46

### APPLICATIONS

- Optical sensor applications
- Optical encoder
- 2D imaging (facial recognition)
- Industrial speed and distance sensors (LIDAR)
- Targeting

### FEATURES

- Single mode VCSEL
- VCSEL chip by **COHERENT**
- Wavelength 850 nm
- Hermetically sealed
- Single transverse and longitudinal mode
- Circular beam profile, Gaussian
- Polarization locked emission
- Compact TO-46 can, with integrated photodiode
- Low power consumption
- High reliability
- RoHS compliant
- Made in Europe

### ABSOLUTE MAXIMUM RATINGS

PARAMETER	MAX RATINGS	UNIT	CONDITIONS
Continuous operating current	8	mA	
Continuous reverse voltage	8	V	
PCB solder or reflow temperature	+260	°C	max. 10 seconds

**Storage temperature: -20°C to +85°C**

**Operating temperature: +5°C to +45°C**

Individual. Innovative. Exceptional.

## Single Mode VCSEL 850 nm

with Photodiode, 1 mW

### ELECTRO-OPTICAL CHARACTERISTICS

PARAMETER	RATINGS			UNIT	CONDITIONS
	MIN	TYP	MAX		
Emission wavelength ( $\lambda_{\text{peak}}$ )	840	850	860	nm	T = +25°C
SM optical output power ( $P_{\text{SM}}$ )	0.9	1		mW	T = +25°C
Side mode suppression ratio (SMSR)	10			dB	T = +25°C, $P_{\text{op}}$ = 0.9 mW
Optical power variation over temperature ( $P(T) - P_{\text{op}}$ )	-200		+120	μW	$I_{\text{op}}$ , T = +5 to +45°C
Beam divergence ( $\theta_{\text{FW1/e}^2}$ )	+12	+17	+21	deg	T = +25°C, $P_{\text{op}}$ = 1 mW
Accuracy of polarization direction* ( $\delta_{\text{pol}}$ )	-15		+15	deg	T = +25°C, $P_{\text{op}}$ = 0.2 to 1 mW
Operating voltage ( $U_{\text{op}}$ )			2.3	V	T = +25°C
Operating current ( $I_{\text{op}}$ )	2.3		6	mA	T = +25°C, $P_{\text{op}}$ = 1 mW
Threshold current ( $I_{\text{th}}$ )	1	3	5	mA	T = +25°C
Slope efficiency ( $\eta$ )	0.20	0.40	0.65	mW/mA	T = +25°C, $P_{\text{op}}$ = 0.2 to 1 mW
Temperature coefficient of wavelength ( $\partial\lambda/\partial T$ )		0.05		nm/K	$I_{\text{op}}$ , T = +5 to +45°C

SM= single mode;  $\text{FW1/e}^2$  = full width 1/e<sup>2</sup>

\* Polarization direction relative to the chip.



$I_{\text{Photodiode}}$ : min. 32 μA, typ. 41 μA; Conditions:  $P_{\text{opt}}$  = 1 mW

Individual. Innovative. Exceptional.


## Single Mode VCSEL 850 nm

with Photodiode, 1 mW

### TYPICAL CHARACTERISTIC CURVES



### TO DIMENSIONS



Placement accuracy  $\pm 150\mu\text{m}$  VCSEL eye to centre of TO cap.  
Placement accuracy  $\pm 60\mu\text{m}$  VCSEL eye to centre of TO header.

### NOTES

Compliant with RoHS-requirements (2011/65/EU from June 8, 2011).

The above product specifications are typical values and subject to change without notice.

Release 12/2025

**WE LOOK  
FORWARD**  
to solving your  
challenge

Individual. Innovative. Exceptional.

IMM Photonics GmbH | Ohmstraße 4 | 85716 Unterschleißheim | Germany | [imm-photonics.de](http://imm-photonics.de)

